# **Section 1: Product & Company Identification**

Product Name: CRC® Engine Degreaser

Product Number (s): 05025, 75025, 85025, 85025AZ

**Product Use:** Engine degreaser

**Manufacturer / Supplier Contact Information:** 

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

2-1246 Lorimar Drive

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394 1-215-674-4300 (General) 1-905-670-2291 www.crc-mexico.com

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

## Section 2: Hazards Identification

### Emergency Overview

52-444-824-1666

**DANGER:** Flammable. Harmful or Fatal if Swallowed. Vapor Harmful. Skin Irritant.

Contents Under Pressure.

Appearance & Odor: Clear, light amber liquid, petroleum odor

### **Potential Health Effects:**

**ACUTE EFFECTS:** 

EYE: Contact with liquid or vapor may cause mild irritation.

SKIN: May cause skin irritation with prolonged or repeated contact. Practically non-toxic if absorbed following

a single exposure.

INHALATION: Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central

nervous system effects may include headache, dizziness, loss of balance and coordination,

unconsciousness, coma, respiratory failure and death.

INGESTION: Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea.

The major health threat of ingestions occurs from the danger of aspiration of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even

death.

CHRONIC EFFECTS: Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly

exposed.

TARGET ORGANS: Central nervous system

Medical Conditions Aggravated by Exposure: Irritation from skin exposure may aggravate existing open wounds, skin

disorders, and dermatitis.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): 05025, 75025, 85025, 85025AZ

# Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Petroleum Distillate	68476-34-6	70 - 80	
Xylene	1330-20-7	10 - 15	
Detergent	68412-54-4	5 - 10	
Ethylbenzene	100-41-4	2 - 4	
Carbon dioxide	124-38-9	< 5	

### **Section 4: First Aid Measures**

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous

vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing

difficulties. Mouth can be rinsed to dissipate the taste.

Note to Physicians: Treat symptomatically.

# **Section 5: Fire-Fighting Measures**

Flammable Properties: This product is flammable in accordance with aerosol flammability definitions.

(See 16 CFR 1500.3(c)(6)).

Flash Point: 115°F / 46°C (TCC) Upper Explosive Limit: 7.5
Autoignition Temperature: ND Lower Explosive Limit: 0.6

Fire and Explosion Data:

Suitable Extinguishing Media: Use extinguishers rated for Class B fires, such as dry chemical, Halon, fire fighting foam

or  $CO_2$ .

Products of Combustion: Oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors

may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

## **Section 6: Accidental Release Measures**

Personal Precautions: Use personal protection recommended in Section 8.

Product Number (s): 05025, 75025, 85025, 85025AZ

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Remove all sources of ignition. Dike area to contain spill. Ventilate the area with

fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents

into proper waste containers.

## **Section 7: Handling and Storage**

Handling Procedures: Keep away from heat, sparks and open flame. Provide adequate ventilation during use. Do not

breathe vapors. Wash hands after use. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product

label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F /

49°C to prevent cans from rupturing. Store in a well ventilated area. Keep out of reach of

children

Aerosol Storage Level: III

# **Section 8: Exposure Controls/Personal Protection**

### **Exposure Guidelines:**

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Petroleum Distillate	5	NE	100	NE	NE		mg/m <sup>3</sup>
Xylene	100	150(v)	100	150	NE		ppm
Detergent	NE	NE	NE	NE	NE		
Ethylbenzene	100	125(v)	100	125	NE		ppm
Carbon dioxide	5000	NE	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

#### **Controls and Protection:**

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also, use full protective clothing if there

is prolonged or repeated contact of liquid with skin.

**Product Number (s): 05025, 75025, 85025, 85025AZ** 

# **Section 9: Physical and Chemical Properties**

Physical State: liquid
Color: light amber
Odor: petroleum
Odor Threshold: ND
Specific Gravity: 0.8667

Initial Boiling Point: 250°F / 121°C

Freezing Point: ND Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: slow

Solubility: emulsifies in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 45.2 g/L: 391.7 lbs./gal: 3.26

# **Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizers, Viton®, Fluorel®

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, non-combusted hydrocarbons (smoke)

Possibility of Hazardous Reactions: No

# **Section 11: Toxicological Information**

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

### **Acute Toxicity:**

<u>Component</u>	Oral LD50 (rat) Dermal LD50 (rabbit)		Inhalation LC50 (rat)	
Petroleum Distillate	9 mL/kg	> 5 mL/kg	No data	
Xylene	3523 mg/kg	> 2000 mg/kg	6700 ppm/4H	
Detergent	1980 mg/kg	No data	No data	
Ethylbenzene	3500 mg/kg	> 5000 mg/kg	4000 ppm/4H	
Carbon dioxide	No data	No data	470,000 ppm/30M	

### **Chronic Toxicity:**

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	Carcinogen	<u>Irritant</u>	Sensitizer
Petroleum Distillate	No	No	No	skin	No
Xylene	No	No	No	skin	Unknown
Detergent	No	No	No	eye, skin	Unknown
Ethylbenzene	No	Group 2B	No	eye, skin	Unknown
Carbon dioxide	No	No	No	No	No

**Product Number (s): 05025, 75025, 85025, 85025AZ** 

Reproductive Toxicity: No information available No information available

Other: Petroleum distillate: This material has been positive in a mutagenicity study.

# **Section 12: Ecological Information**

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Xylene - 96 Hr LC50 fathead minnow: 13.4 mg/L (flow-through)

Ethylbenzene - 48 Hr EC50 water flea: 2.1 mg/L

Persistence / Degradability: No information available Bioaccumulation / Accumulation: No information available

Mobility in Environment: Spills may penetrate the soil causing groundwater contamination. This material may

accumulate in sediments.

# **Section 13: Disposal Considerations**

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for the characteristic of flammability

with a waste code of D001. (See 40 CFR Part 261.20 – 261.33). Aerosol containers should be emptied and depressurized before disposal. Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

# **Section 14: Transport Information**

US DOT (ground): UN1950, Aerosols, flammable, 2.1, Limited Quantity\*\*

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: \*\*This product can be classified and labeled as 'Consumer Commodity, ORM-D' for domestic

ground shipping until January 1, 2014.

If shipping as limited quantity by ground, note that shipping papers are not required.

# **Section 15: Regulatory Information**

### **U.S. Federal Regulations:**

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Xylene (100 lbs), Ethylbenzene (1000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Product Number (s): 05025, 75025, 85025, 85025AZ

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No Release of Pressure Yes Acute Health Hazard Yes Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

Xylene (12%), Ethylbenzene (3%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Xylene, Ethylbenzene

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

**U.S. State Regulations:** 

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: Ethylbenzene,

Naphthalene (< 0.01%)

Consumer Products VOC Regulations: This product does not comply with Consumer Products VOC regulations and

cannot be used in California, Connecticut, Delaware, The District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New Hampshire, New York, Ohio, Pennsylvania, Rhode Island, and parts of Virginia.

State Right to Know:

New Jersey: 1330-20-7, 100-41-4 Pennsylvania: 1330-20-7, 100-41-4 Massachusetts: 1330-20-7, 100-41-4 Rhode Island: 1330-20-7, 100-41-4

**Canadian Regulations:** 

**Controlled Products Regulations:** 

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2A, D2B

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.

**European Union Regulations:** 

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as

listed in Article 4(1) of the RoHS Directive.


Additional Regulatory Information: None

Product Number (s): 05025, 75025, 85025, 85025AZ

## **Section 16: Other Information**

HMIS® (II)		
Health:	2	
Flammability:	2	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 567E Revision Date: 05/21/2012

Changes since last revision: Section 11: Toxicological Information

Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization

lbs./gal: pounds per gallon LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit TCC: Tag Closed Cup TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System