



1. Product Description

Sta Lube® Equa-Torque™ friction gear oil additive is designed to prevent/eliminate chattering and jerking common to limited slip and "posi" differentials. Required in many domestic rear wheel drive vehicles.

II. Applications

Should be used in conjunction with conventional GL-5 or HP level gear oils.

DO NOT USE IN AMC JEEPS WITH QUADRA-TRAC.

III. Features & Benefits

- Prevents chattering, jerking and slipping.
- Available in 4 ounce size container.
- Meets OEM specifications

IV. Physical Properties

Flash Point	≥310 °F COC	Boiling Point (initial)	>600 °F
Odor	Faint Petroleum	Solubility	Negligible
Appearance	Clear Amber Liquid	% Volatile	Negligible
Vapor Density	> Air	Specific Gravity	.92
Prop 65	No	Vapor Pressure	Negligible
Sara Title III, Sect. 313 Chemicals	No	VOC	3%

V. Specifications and Approvals

ASTM D-445 Kinematic Viscosity @ 100°C	6.3
ASTM D-92 Flash Point, °F	≥310

Meets performance specifications for limited-slip additives for GM1052358, Ford M2C118-A, Chrysler 4318060 and most imports.

Recommended by Rockwell for use in traction equalizers.

VI. Directions

Empty contents into differential housing filler opening.

4 ounces is normal dosage required to remedy problem for limited-slip axles.

CAUTION: Poor or faulty performance may result if other additives are combined with Equa-Torque in limited-slip differentials.

VII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

VIII. Special Use Warnings

General

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure; review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

*CRC Industries, Inc.
Technical Service: (800)521-3168*

*Sta-Lube Products Division
Customer Service: (800)272-8963*

*Warminster, PA 18974
CRC On-Line: (215)442-6260*