Section 1: Product & Company Identification

Product Name: Power Steering Fluid - Universal

Product Number (s): SL2651

Product Use: Power steering fluid

Manufacturer / Supplier Contact Information:

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394 1-215-674-4300(General) 1-905-670-2291 <u>www.crc-mexico.com</u>

1-215-674-4300(General) (800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Appearance & Odor: Red liquid, faint petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Eye contact may result in light irritation and redness.

SKIN: Short term contact with skin is unlikely to cause any problems. Excessive or repeated contact

and poor hygiene conditions may result in dryness, dermatitis, erythema, oil acne, cracking and

52-444-824-1666

defatting of the skin.

INHALATION: Inhalation of vapors or mist may be irritating to the respiratory passages. Prolonged exposure

may result in dizziness and nausea.

INGESTION: May result in nausea or stomach discomfort.

CHRONIC EFFECTS: None known

TARGET ORGANS: lungs (oil mist)

Medical Conditions Aggravated by Exposure: pre-existing skin disorders

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: Power Steering Fluid - Universal Product Number (s): SL2651

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Hydrotreated heavy naphthenic oil	64742-52-5	88 – 98	
Additive blend	proprietary	2 – 6	
Toluene	108-88-3	< 0.1	

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: If swallowed, observe for signs of stomach discomfort or nausea. If symptoms persist, seek

medical help. Do not induce vomiting. If there is any suspicion of aspiration into lungs, obtain

immediate medical attention.

Note to Physicians: Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is a Class IIIB Combustible Liquid (not regulated).

Flash Point: > 290°F (SETA) Upper Explosive Limit: ND
Autoignition Temperature: > 600°F Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Halon, dry chemical, foam, CO2, water mist or fog, or any Class B extinguishing agent.

Products of Combustion: Fumes, smoke, carbon monoxide

Explosion Hazards: Containers, when exposed to heat from fire, may build pressure and rupture.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space

or limited air circulation area, clean-up workers should wear appropriate

respiratory protection. Recover or absorb spilled material using an absorbent

designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from flames, sparks or hot surfaces. Wash thoroughly after handling and before

handling food. Use proper grounding and bonding techniques when transferring material. For

product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in

storage.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OS	SHA	AC	GIH	0	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Hydrotreated naphthenic oil	5*	NE	5*	10*	NE		mg/m ³
Additive blend	NE	NE	NE	NE	NE		
Toluene	200	300	20	NE	NE		ppm
N.E. – Not Established	(c) – ce	iling (s)	– skin	(v) – vad	cated	* – oil mist	

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined

spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: red

Odor: faint petroleum
Odor Threshold: ND
Specific Gravity: 0.904
Initial Boiling Point: ND
Freezing Point: ND
Vapor Pressure: ND

Product Name: Power Steering Fluid - Universal

Vapor Density: > 5 (air = 1)

Evaporation Rate: slow Solubility: negligible

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: < 0.1 g/L: < 1 lbs./qal: < 0.01

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition

Incompatible Materials: Strong oxidizers, halogens

Hazardous Decomposition Products: Oxides of carbon and nitrogen; aldehydes

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

Component	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Hydrotreated naphthenic oil	> 5000 mg/kg	> 2000 mg/kg	2.18 mg/L/4H
Additive blend	No data	No data	No data
Toluene	636 mg/kg	14,100 μL/kg	49 mg/m ³ /4H

Chronic Toxicity:

	OSHA	IARC	NTP		
Component	Carcinogen	Carcinogen	Carcinogen	<u>Irritant</u>	<u>Sensitizer</u>
Hydrotreated naphthenic oil	No	No	No	E (mild) / S (mild)	No
Additive blend	No	No	No	Unknown	Unknown
Toluene	No	No	No	E (mild) / S (mild) /	Unknown
				R (mild)	

E – Eye S – Skin R - Respiratory

Product Number (s): SL2651

Reproductive Toxicity: No information available Teratogenicity: No information available

Mutagenicity: Hydrotreated naphthenic oil: Mutagenic index of less than 1.0

Synergistic Effects: No information available

Other: IARC has determined in reviewing cancer prevalence of exposed workers that

the carcinogenic activity of refined oils is related to the severity of processing of the base oil. The base oils contained in this product have been highly refined to remove aromatic, thus reducing carcinogenic potential. IP346: DMSO < 3.0%

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Hydrotreated naphthenic oil – 96 Hr LC50, Fathead minnow: > 30,000 mg/L (static)

Product Name: Power Steering Fluid - Universal

Persistence / Degradability: This product is not readily biodegradable.

Bioaccumulation / Accumulation: No information available Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)

Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Product Number (s): SL2651

Section 14: Transport Information

US DOT (ground): Not Regulated

ICAO/IATA (air): Not Regulated

IMO/IMDG (water): Not Regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No Release of Pressure No Acute Health Hazard No Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Product Name: Power Steering Fluid - Universal Product Number (s): SL2651

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

Toluene (0.09%)

<u>Consumer Products VOC Regulations</u>: This product is not regulated.

State Right to Know:

New Jersey: 108-88-3 Pennsylvania: 108-88-3 Massachusetts: 108-88-3 Rhode Island: 108-88-3

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: None

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as


listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)		
Health:	1	
Flammability:	1	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 910A Revision Date: 02/10/2009

Changes since last revision: New formula

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

Product Number (s): SL2651

Product Name: Power Steering Fluid - Universal

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer

IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization

lbs./gal: pounds per gallon LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System